常 用
Residential

普通系列
Ordinary Series

AS 款 AS Series

- 机器人焊接机架，一致性好
  Robot frame welding process enssures good consistency
- 专业防水设计
  Professional water-proof design
- 专用消声器内腔设计，降低噪音
  Special muffler chamber design, lower noise
- 专利外观设计，结构紧凑
  Patent exterior design, compact structure

产品参数
Specifications

机型 Model	LC2500(D)-AS	LC3000(D)-AS	LC3500(D)-AS
发动机型号 Engine model	LC168FD-2		G210FDA
排量 Displacement(cc)	196		212
燃油箱容量 Fuel tank capacity(L)	18		
燃油连续工作时间(1/2 负载 load) Running time(h)	15		
额定频率 Rated frequency(Hz)	50/60		
额定电压 Rated voltage(V)	110/120/220/230		
发电机类型 Generator Type	普通开架 Open frame Generator		
运行功率 Running Power(kW)	2	2.3	2.8/3.0
启动功率 Starting Power(kW)	2.2	2.5	3.1/3.3
功率因数 Power factor	1		
启动类型 Starting Type	手 Recoil start / 电 Electric start		
噪声值 Noise(dbA)7m	≤ 72	≤ 74	
净重 Net weight(kg)	39/41	45/47	45.5/47.5
外形尺寸(长×宽 ×高) Product Dimension(L × W × H)mm	590×430×467		
包装尺寸(长×宽 ×高) Packing Dimension(L × W × H)mm	605×445×495		

常 用
Residential

普通系列
Ordinary Series

AS 款 AS Series

- 机器人焊接机架，一致性好
  Robot frame welding process enssures good consistency
- 专业防水设计
  Professional water-proof design
- 专用消声器内腔设计，降低噪音
  Special muffler chamber design, lower noise
- 专利外观设计，结构紧凑
  Patent exterior design, compact structure

产品参数
Specifications

机型 Model	LC5000(D)-AS	LC6500(D)-AS	LC8000(D)-AS	LC10000(D)-AS
发动机型号 Engine model	LC188FD		LC190FD-1	LC192FD
排量 Displacement(cc)	389		420	459
燃油箱容量 Fuel tank capacity(L)	25			
燃油连续工作时间(1/2 负载 load) Running time(h)	10	9	8	
额定频率 Rated frequency(Hz)	50/60			
额定电压 Rated voltage(V)	110/120/220/230			
发电机类型 Generator Type	普通开架 Open frame Generator			
运行功率 Running Power(kW)	4	5	6/6.5	7.3/7.8
启动功率 Starting Power(kW)	5	5.5	6.5/7	8/8.5
功率因数 Power factor	1			
启动类型 Starting Type	手 Recoil start / 电 Electric start			
噪声值 Noise(dbA)7m	≤ 76		≤ 78	
净重 Net weight(kg)	73/75	77/79	/	/
外形尺寸(长×宽 ×高) Product Dimension(L × W × H)mm	681×546×550			
包装尺寸(长×宽 ×高) Packing Dimension(L × W × H)mm	700×560×585			

商　用
Commercial

工业款
Industrial Series

■ 高强度油箱设计，满足承重 >75Kg 不损坏，30L 大容量油箱，连续运行时间 >8h
Robust fuel tank design, carry weight more than 75kg, 30L big capacity, running hours >8h.

■ 金属护板设计，框架牢实，加强空滤器设计，可靠性提升，满足连续 1000h 耐久试验，首次故障率时间 >500h
Metal side panel design, sturdy frame, strengthened air cleaner. Passed 1000h durability. No failure occurred during the first 500h

■ 全系感性电机，启动水泵及风机的能力提升 6% ~ 10%
Whole series of inductive alternator enables starting performance increase by 6%~10%

产品参数
Specifications

机型 Model	LC2500(D)-S	LC3500(D)-S	LC6500(D)-S	LC8000(D)-S	LC10000(D)-S
发动机型号 Engine model	LC168FD-2	G210FDA	LC188FD	LC190FD-1	LC192FD
排量 Displacement(cc)	196	212	389	420	459
燃油箱容量 Fuel tank capacity(L)	18		30		
燃油连续工作时间 (50%额定功率 Rated Power) Running time(h)	20	17.5	14	13	11
额定频率 Rated frequency(Hz)	50				
额定电压 Rated voltage(V)	220/230				
发电机类型 Generator Type	普通开架 Open frame Generator				
运行功率 Running Power(kW)	2.2	3.1	5.5	6.5	8
启动功率 Starting Power(kW)	2.5	3.5	6.5	8	10
功率因数 Power factor	1				
启动类型 Starting Type	手 Recoil start/ 电 Electric start				
噪声值 Noise(dbA)7m	≤ 70		≤ 75		
净重 Net weight(kg)	45/47	47/49	77.5/79.5	84/86	92/94
外形尺寸(长×宽 ×高) Product Dimension(L × W × H)mm	590×475×467		695×546×550		
包装尺寸(长×宽 ×高) Packing Dimension(L × W × H)mm	605×490×495		710×590×580		

商　用
Commercial

通讯款
Communication Industry Series

■ 高强度 40L 超大油箱设计，全新国二化油器，油耗更低，满载连续运行时间 >9.5h
Robust 40L fuel tank , All-new carburetor, low fuel consumption and running hours >9.5h at full load.

■ 数字点火器 + 数字调压器 + 电子调速系统，电源质量大幅提高，通讯行业专用发电机
Telecom industry generator equipped with digital ignition&regulator, E- throttle system, all together greatly increase the power quality.

■ 搬运扶手 + 四车轮设计，方便移动
Moving Handle+4 wheel design, easy to move around

■ 满负荷连续不间断运行 500 小时无故障
Continuously running for 500h without failure at full load

■ 可选配内置式 SIM 卡，通过 GSM 网络，使用手机 APP 远程控制发电机组的启动和停机，并时时监控发电机状态
Mobile APP can start, stop and monitor the generator in real time through GSM network(SIM required)

产品参数
Specifications

机型 Model	LC10000-T	LC13000-T	LC18000-T	LC22000-T	LC24000-T
发动机型号 Engine model	LC192FD	LC196FD	LC2V80FD	LC2V90FD	
排量 Displacement(cc)	459	622	764	999	
燃油箱容量 Fuel tank capacity(L)	40	48	40		
燃油连续工作时间 (50%额定功率 Rated Power) Running time(h)	16	8		6	
额定频率 Rated frequency(Hz)	50/60				
额定电压 Rated voltage(V)	110/120/220/230				
发电机类型 Generator Type	普通开架 Open frame Generator				
运行功率 Running Power(kW)	8	10	13/14	16/17.5	18/20
启动功率 Starting Power(kW)	10	13	17/18	20/22	22/24
功率因数 Power factor	1				
启动类型 Starting Type	手 Recoil start/ 电 Electric start		电 Electric start		
噪声值 Noise(dbA)7m	≤ 75	≤ 80			
净重 Net weight(kg)	90/96	143	198	213	236
外形尺寸(长×宽 ×高) Product Dimension(L × W × H)mm	695×546×550	850×620×650(含 车 轮 宽 785 高 788 Include wheel 850*785*788)	1034×860×715(含 车 轮 高 860 Wheels included 860)		
包装尺寸(长×宽 ×高) Packing Dimension(L × W × H)mm	710×590×580	920×645×675	1080×710×880		